



**D5643-1 SADDLE SPACER**

**UNDER REVIEW**  
URF 19-746 19.05.28 (NO)

**NOTES:**

- 1) MATERIAL: 6061-T6/T62/T651 PER QQ-A-250/11 OR AMS-QQ-A-250/11  
OR AMS 4025 OR AMS 4027 OR ASTM B209  
ALUMINUM SHEET 0.080 THICK, REF DART SPEC M6061T6S.080  
OR  
5052-H32 PER QQ-A-250/8 OR AMS-QQ-A-250/8  
OR AMS 4016 OR ASTM B209  
ALUMINUM SHEET 0.080 THICK, REF DART SPEC M5052H32S.080
- 2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1
- 3) TOLERANCES PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY PER DART QSI 044 6.1
- 7) WEIGHT: 0.02 lb
- 8) ALL NON DIMENSIONED FEATURES PER CAD FILE "D5643-1-REVA.DXF"

APPROVED

A	NEW ISSUE		ZF	18.04.25
REV.	DESCRIPTION		BY	DATE
DESIGN	ZF	<b>DART AEROSPACE LTD</b> HAWKESBURY, ONTARIO, CANADA		
DRAWN	ZF			
CHECKED	MW	DRAWING NO. <b>D5643</b>		REV. A
MFG. APPR.	DD			SHEET 1 OF 1
APPROVED	NO	TITLE		SCALE
DE APPR.	CP	<b>SADDLE SPACER</b>		NTS
DATE	18.04.25		COPYRIGHT © 2018 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	